



PF9600 Automatic Swing Gate

The **PF9600 Automatic Swing Gates** comply with BS/EN 12453 (the current legislation ALL automated gates must comply with). We fit as standard a number of safety devices, including dual height photo cells and Category 3 safety edges.

be ordered to be bolt down if required.

The very neat precise housing design accommodates the control panel within the column. This gives a smooth finished appearance unlike other automated systems which often have an additional obtrusive housing.

The gates are controlled by a purpose made controller, **single** phase supply, via an inverter controlled output to a 3 phase motor. This can be configured very easily for all the standard program modes including no passage time outs & free exit and entry loops to name a few.

The best feature of our gates is that they are fully assembled ready to bolt down and as soon as they are commissioned they are fully compliant to all standards. This minimises disruption on site and leaves a beautifully finished product which will serve for many years.

TECHNICAL SPECIFICATION

Specification

CE Approved BS/EN 12453

Maximum Span

8 Metres Drive-Through

Maximum Height

3 Metres

Finish

Zinc plated and polyester powder coated

Power Requirement

SINGLE phase 240Volt 50Hz 10 amp

Drive Motor

3 phase motor and wormed gearbox

Duty Cycles

100% Continuous Duty Rating

Operation Time

4 - 8 seconds (dependant on version)